

FIRE RESISTANT SAFES

BURGLARY & FIRE RESISTANT SAFES



SB-02C



SBE-02K



SBS-1100CC

LOCK OPTIONS



SB

**U.L. RATED
BURGLARY/
FIRE SAFES**

The best choice to protect your property from fire and burglary



- 1 hour fire protection and premium security(UL Class 350 1 hour, UL 1037 RSC)
- Heavy duty composite construction - 2" thick door and 3" thick body
- Independent glass re-locking device
- Three stationary locking bolts on hinge side to deter prying attack on hinges
- Heavy duty steel hinge
- 3 spoke chrome-plated vault handle
- Reinforced composite body with concrete and steel mesh(Optional)
- Pre-drilled anchor hole(Optional)



SB SERIES DIMENSIONS

Model	Outside(mm)			Inside(mm)			Weight (Kgs)	Outside(inch)			Inside(inch)			Weight (lbs)	Shelf	UL 1 hour	UL RSC
	H	W	D	IH	IW	ID		H	W	D	IH	IW	ID				
SB-01E SB-01C	450	450	520	305	305	318	75	17 5/7	17 5/7	20 1/2	12	12	12 1/2	165	1	*	*
SB-02E SB-02C	685	508	520	540	363	327	168	27	20	20 1/2	21 1/4	14 2/7	12 7/8	370	2	*	*
SB-03E SB-03C	845	508	578	700	363	385	276	33 1/4	20	22 3/4	27 5/9	14 2/7	15 1/6	607	2		*
SB-04E SB-04C	845	710	737	700	565	544	360	33 1/4	28	29	27 5/9	22 1/4	21 3/7	792	2		*
SB-05E SB-05C	1054	710	737	910	565	544	420	41 1/2	28	29	35 5/6	22 1/4	21 3/7	924	2		*
SB-06E SB-06C	1505	710	737	1361	565	544	480	59 1/4	28	29	53 4/7	22 1/4	21 3/7	1056	3		*